

De Dietrich

Hood

Ref.: **DHV4674B**

atmosphere of your room and to your needs.



Product highlights

Top-of-the-line design This new hood combines design, technology and functionality. An elegant glass panel, exceptional performances and a host of innovations: discover unrivalled mastery in an exceptional minimalist setting.

Booster Thanks to its powerful brushless motor, the hood guarantees rapid elimination of unwanted fumes and odors in intensive mode.

LED dimmer This function allows you to adjust the light of your hood on 3 levels in order to adapt it to the

GENERAL

Brand	DE DIETRICH
Commercial code	DHV4674B
EAN code	3660767999503
Customs code	84146000

FEATURES

Product type	Wall decorative hood
Design type	Vertical
Width (cm)	60
Finishing	Glass
Colour	Black
Air vented mode	Recycling or extracting air
Delivered in	Recycling air
Type of engine	Brushless
Total power of the motors (W)	160
Number of motors	1
Motor location	In hood
Delayed stop	Yes
LED dimmer	Yes
Fan quantity	1

PERFORMANCE

Annual energy consumption (kW/h)	33
Energy efficiency class	A+
Min extraction rate (m3/h)	225
Max extraction rate (m3/h)	550
Extraction rate with boost (m3/h)	745
Min recirculation rate (m3/h)	80
Max recirculation rate (m3/h)	265
Recirculation rate with boost (m3/h)	440
Min noise level (dB) (Extraction)	40
Max noise level (dB) (acoustic pressure)	60
Noise level with Boost (dB) (Extraction)	69
Min noise level (dB) (recirculation)	42
Max noise level (dB) (recirculation)	64
Noise level with Boost (dB) (recirculation)	75
Fluid dynamic efficiency class	A
Light efficiency class	C
Lighting efficiency (Lux)	121
Grease filter efficiency class	E

De Dietrich

Hood

Ref.: DHV4674B

CONTROLS & LIGHTS

Control type	Backlit electronic controls
Number of speed positions (without booster)	3
Booster	Yes
Filters saturation indicator	No
Type of light	Adjustable leds
Number of lights	2
Total power of the lamps (W)	7

EQUIPMENT

Type of functions	Delayed stop;Light;Speed;On/Off
Number of grease filters	
Grease filter material	Dishwasher safe aluminium
Accessories supplied	Chimney
Reference of charcoal filter	FWND-185
Reference of recycling kit	
Optional accessories	Charcoal filter
Reference of engine	
Reference of the chimney extension	
Air outled diameter (mm)	150
Deflector	No
Non-return valve	Yes

INSTALLATION

Fuse (A)	1.18
Voltage (V)	220-240
Frequency (Hz)	50-60
Other functions	
Dimensions of the product without chimney HxWxD (mm)	347X600X392
Min-max chimney height (mm)	573/940
Dimensions of the packed product HxWxD (mm)	500X700X500
Net weight (kg)	15.6
Gross weight (kg)	21.2

MANUFACTURING

Availability of spare parts (years)	15
Repair index	