

De Dietrich

Hood

Ref.: **DHV4974HB**



Product highlights

Air purifier De Dietrich's ingenious new air purifier with HEPA filter cleans the air in your kitchen. Activated whenever you want, it detects air quality and eliminates harmful particles, for a consistently healthy environment.

Top-of-the-line design This new hood combines design, technology and functionality. An elegant glass panel, exceptional performances and a host of innovations: discover unrivalled mastery in an exceptional minimalist setting.

HIGH Performance This hood is classified Energy Label A+. It is the result of a perfectly accomplished design and offers the best in terms of energy savings and efficiency,

GENERAL

| | |
|-----------------|---------------|
| Brand | DE DIETRICH |
| Commercial code | DHV4974HB |
| EAN code | 3660767996496 |
| Customs code | 84146000 |

FEATURES

| | |
|-------------------------------|-----------------------------|
| Product type | Wall decorative hood |
| Design type | Vertical |
| Width (cm) | 90 |
| Finishing | Glass |
| Colour | Black |
| Air vented mode | Recycling or extracting air |
| Delivered in | Air extraction |
| Type of engine | Brushless |
| Total power of the motors (W) | 160 |
| Number of motors | 1 |
| Motor location | In hood |
| Delayed stop | Yes |
| LED dimmer | Yes |
| Fan quantity | 1 |

PERFORMANCE

| | |
|---|-----|
| Annual energy consumption (kWh) | 33 |
| Energy efficiency class | A+ |
| Min extraction rate (m3/h) | 225 |
| Max extraction rate (m3/h) | 550 |
| Extraction rate with boost (m3/h) | 745 |
| Min recirculation rate (m3/h) | 80 |
| Max recirculation rate (m3/h) | 265 |
| Recirculation rate with boost (m3/h) | 440 |
| Min noise level (dB) (Extraction) | 40 |
| Max noise level (dB) (acoustic pressure) | 60 |
| Noise level with Boost (dB) (Extraction) | 69 |
| Min noise level (dB) (recirculation) | 42 |
| Max noise level (dB) (recirculation) | 64 |
| Noise level with Boost (dB) (recirculation) | 75 |
| Fluid dynamic efficiency class | A |
| Light efficiency class | C |
| Lighting efficiency (Lux) | 121 |
| Grease filter efficiency class | E |

De Dietrich

Hood

Ref.: DHV4974HB

| CONTROLS & LIGHTS | |
|---|-----------------------------|
| Control type | Backlit electronic controls |
| Number of speed positions (without booster) | 3 |
| Booster | Yes |
| Filters saturation indicator | No |
| Type of light | Led stripe |
| Number of lights | 1 |
| Total power of the lamps (W) | 7 |

| EQUIPMENT | |
|------------------------------------|---------------------------------|
| Type of functions | Delayed stop;Light;Speed;On/Off |
| Number of grease filters | 2 |
| Grease filter material | Dishwasher safe aluminium |
| Accessories supplied | Chimney |
| Reference of charcoal filter | FWND-185 |
| Reference of recycling kit | |
| Optional accessories | Charcoal filter |
| Reference of engine | |
| Reference of the chimney extension | |
| Air outled diameter (mm) | 150 |
| Deflector | No |
| Non-return valve | Yes |

| INSTALLATION | |
|--|--------------|
| Fuse (A) | 1.28 |
| Voltage (V) | 220-240 |
| Frequency (Hz) | 50-60 |
| Other functions | |
| Dimensions of the product without chimney HxWxD (mm) | 400X900X404 |
| Min-max chimney height (mm) | 575/905 |
| Dimensions of the packed product HxWxD (mm) | 500X1000X550 |
| Net weight (kg) | 22 |
| Gross weight (kg) | 26.2 |

| MANUFACTURING | |
|-------------------------------------|----|
| Availability of spare parts (years) | 15 |
| Repair index | |