

# De Dietrich

## Hood

Ref.: DHL2993W



## Product highlights

**Ceiling hood** This hood is installed directly in the ceiling above your hob. Thanks to its large size, it will capture vapors and odors perfectly.

**Remote Control** It allows you to regulate lighting, functioning and extraction power from distance.

**LED dimmer** This function allows you to adjust the light of your hood on 3 levels in order to adapt it to the atmosphere of your room and to your needs.

### GENERAL

Brand	DE DIETRICH
Commercial code	DHL2993W
EAN code	3660767988019
Customs code	84146000

### FEATURES

Product type	Ceiling hood
Design type	Ceiling
Width (cm)	90
Finishing	Glass
Colour	White
Air vented mode	
Delivered in	
Type of engine	
Total power of the motors (W)	170
Number of motors	1
Motor location	
Delayed stop	Yes
LED dimmer	
Fan quantity	

### PERFORMANCE

Annual energy consumption (kW/h)	42,4
Energy efficiency class	A
Min extraction rate (m3/h)	160
Max extraction rate (m3/h)	450
Extraction rate with boost (m3/h)	700
Min recirculation rate (m3/h)	
Max recirculation rate (m3/h)	
Recirculation rate with boost (m3/h)	
Min noise level (dB) (Extraction)	44
Max noise level (dB) (acoustic pressure)	64
Noise level with Boost (dB) (Extraction)	70
Min noise level (dB) (recirculation)	
Max noise level (dB) (recirculation)	
Noise level with Boost (dB) (recirculation)	
Fluid dynamic efficiency class	A
Light efficiency class	A
Lighting efficiency (Lux)	290
Grease filter efficiency class	D

# De Dietrich

## Hood

Ref.: DHL2993W

### CONTROLS & LIGHTS

Control type	Remote Control
Number of speed positions (without booster)	3
Booster	
Filters saturation indicator	No
Type of light	Led stripe
Number of lights	2
Total power of the lamps (W)	10

### EQUIPMENT

Type of functions	Delayed stop;Independent lighting;On/Off
Number of grease filters	2
Grease filter material	Washable aluminium
Accessories supplied	
Reference of charcoal filter	Pas de référence
Reference of recycling kit	
Optional accessories	
Reference of engine	
Reference of the chimney extension	
Air outled diameter (mm)	150 / 120
Deflector	No
Non-return valve	Yes

### INSTALLATION

Fuse (A)	0.98
Voltage (V)	220-240
Frequency (Hz)	50/60
Other functions	
Dimensions of the product without chimney HxWxD (mm)	187X900X600
Min-max chimney height (mm)	/
Dimensions of the packed product HxWxD (mm)	725X1010X370
Net weight (kg)	19.5
Gross weight (kg)	25.2

### MANUFACTURING

Availability of spare parts (years)	15
Repair index	