

De Dietrich

Hood

Ref.: DHB361BX



Product highlights

Automatic extraction In case of smoke detection, the hood activates air extraction instantly. The debit is regulated automatically within speed 1 and speed 4.

Electronic soft touch controls The light and air flow regulation is done by a simple one-finger touch on the sensitiv button made of glass. The comfort is guaranteed while the purity of shapes is preserved.

Booster Thanks to its powerful brushless motor, the hood guarantees rapid elimination of unwanted fumes and odors in intensive mode.

GENERAL

Brand	DE DIETRICH
Commercial code	DHB361BX
EAN code	3660767990852
Customs code	84146000

FEATURES

Product type	Wall decorative hood
Design type	Slim box
Width (cm)	60
Finishing	Stainless steel+glass
Colour	Stainless steel
Air vented mode	Recycling or extracting air
Delivered in	Air extraction
Type of engine	
Total power of the motors (W)	160
Number of motors	1
Motor location	In hood
Delayed stop	Yes
LED dimmer	
Fan quantity	

PERFORMANCE

Annual energy consumption (kWh)	40
Energy efficiency class	A+
Min extraction rate (m3/h)	210
Max extraction rate (m3/h)	530
Extraction rate with boost (m3/h)	715
Min recirculation rate (m3/h)	70
Max recirculation rate (m3/h)	310
Recirculation rate with boost (m3/h)	395
Min noise level (dB) (Extraction)	45
Max noise level (dB) (acoustic pressure)	65
Noise level with Boost (dB) (Extraction)	72
Min noise level (dB) (recirculation)	40
Max noise level (dB) (recirculation)	67
Noise level with Boost (dB) (recirculation)	73
Fluid dynamic efficiency class	A
Light efficiency class	A
Lighting efficiency (Lux)	480
Grease filter efficiency class	E

CONTROLS & LIGHTS

Control type	Electronic touch-sensitive controls
Number of speed positions (without booster)	3
Booster	
Filters saturation indicator	No
Type of light	LED
Number of lights	2
Total power of the lamps (W)	8

De Dietrich

Hood

Ref.: **DHB361BX**

EQUIPMENT	
Type of functions	Speed;Light;Delayed stop
Number of grease filters	2
Grease filter material	Dishwasher safe aluminium
Accessories supplied	Chimney
Reference of charcoal filter	FWND-185
Reference of recycling kit	
Optional accessories	Charcoal filter
Reference of engine	
Reference of the chimney extension	
Air outlet diameter (mm)	150
Deflector	No
Non-return valve	Yes

INSTALLATION	
Fuse (A)	1.24
Voltage (V)	220-240
Frequency (Hz)	50-60
Other functions	
Dimensions of the product without chimney HxWxD (mm)	40X600X406
Min-max chimney height (mm)	730/935
Dimensions of the packed product HxWxD (mm)	475X700X570
Net weight (kg)	11
Gross weight (kg)	13.8

MANUFACTURING	
Availability of spare parts (years)	15
Repair index	